

# スピードコントロールモーター オリエンタルモーター(株)

208441

## MSS-W形レバーシプルモーター仕様・価格(本体価格のみ)

30分定格

品名・タイプ			仕様	最大出力 W	電圧 V	周波数 Hz	可変速度範囲 r/min	許容トルク mN・m		起動トルク mN・m	電流 A	消費電力 W	適用コントロール品名
歯切シャフト	丸シャフト	価格						1200 r/min	90 r/min				
MSS206-411W2J	MSS206-011W2J	27,100	Ⓢ	6	単相100	50 90~1400	50	50	50	0.3	30	MSP-1W	
			60 90~1600			0.32				30			
MSS206-411W2U	MSS206-011W2U	27,100	Ⓢ	6	単相110	50 90~1400	50	50	50	0.31	32	MSP-1W	
			60 90~1600			0.32				32			
MSS315-411W2J	MSS315-011W2J	27,650	Ⓢ	15	単相100	50 90~1400	125	110	110	0.64	60	MSP-1W	
			60 90~1600			0.64				60			
MSS315-411W2U	MSS315-011W2U	27,650	Ⓢ	15	単相110	50 90~1400	125	94	110	0.63	65	MSP-1W	
			60 90~1600			0.63				65			
MSS425-411W2J	MSS425-011W2J	28,500	Ⓢ	25	単相100	50 90~1400	205	125	145	0.98	92	MSP-1W	
			60 90~1600			0.98				92			
MSS425-411W2U	MSS425-011W2U	28,500	Ⓢ	25	単相110	50 90~1400	205	100	145	0.97	97	MSP-1W	
			60 90~1600			0.97				97			
MSS540-411W2J	MSS540-011W2J	30,050	Ⓢ	40	単相100	50 90~1400	320	180	235	1.5	135	MSP-1W	
			60 90~1600			1.5				135			
MSS540-411W2U	MSS540-011W2U	30,050	Ⓢ	40	単相110	50 90~1400	320	145	235	1.5	140	MSP-1W	
			60 90~1600			1.5				140			
MSS560-511W2J	MSS560-011W2J	37,500	Ⓢ	60	単相100	50 90~1400	490	360	410	2.3	195	MSP-1W	
			60 90~1600			2.3				187			
MSS560-511W2U	MSS560-011W2U	37,500	Ⓢ	60	単相110	50 90~1400	490	260	410	2.2	197	MSP-1W	
			60 90~1600			2.2				199			
MSS590-511W2J	MSS590-011W2J	41,750	Ⓢ	90	単相100	50 90~1400	730	320	540	2.9	230	MSP-1W	
			60 90~1600			2.9				245			
MSS590-511W2U	MSS590-011W2U	41,750	Ⓢ	90	単相110	50 90~1400	730	300	540	2.9	254	MSP-1W	
			60 90~1600			2.9				251			
MSS206-412W2J	MSS206-012W2J	27,300	Ⓢ	6	単相200	50 90~1400	45	50	50	0.16	30	MSP-2W	
			60 90~1600			0.16				30			
MSS206-412W2E	MSS206-012W2E	27,300	Ⓢ	6	単相220	50 90~1400	50	50	50	0.15	32	MSP-2W	
			60 90~1600			0.15				32			
MSS315-412W2J	MSS315-012W2J	27,850	Ⓢ	15	単相200	50 90~1400	125	90	100	0.31	64	MSP-2W	
			60 90~1600			0.31				64			
MSS315-412W2E	MSS315-012W2E	27,850	Ⓢ	15	単相220	50 90~1400	125	90	104	0.31	64	MSP-2W	
			60 90~1600			0.31				64			
MSS425-412W2J	MSS425-012W2J	28,800	Ⓢ	25	単相200	50 90~1400	205	115	150	0.52	92	MSP-2W	
			60 90~1600			0.52				92			
MSS425-412W2E	MSS425-012W2E	28,800	Ⓢ	25	単相220	50 90~1400	205	115	145	0.51	95	MSP-2W	
			60 90~1600			0.51				95			
MSS540-412W2J	MSS540-012W2J	30,350	Ⓢ	40	単相200	50 90~1400	320	145	260	0.75	135	MSP-2W	
			60 90~1600			0.75				135			
MSS540-412W2E	MSS540-012W2E	30,350	Ⓢ	40	単相220	50 90~1400	320	145	260	0.75	140	MSP-2W	
			60 90~1600			0.75				140			
MSS560-512W2J	MSS560-012W2J	37,900	Ⓢ	60	単相200	50 90~1400	490	250	440	1.1	183	MSP-2W	
			60 90~1600			1.1				190			
MSS560-512W2E	MSS560-012W2E	37,900	Ⓢ	60	単相220	50 90~1400	490	250	440	1.0	194	MSP-2W	
			60 90~1600			1.0				199			
MSS590-512W2J	MSS590-012W2J	42,150	Ⓢ	90	単相200	50 90~1400	730	260	540	1.3	235	MSP-2W	
			60 90~1600			1.4				248			
MSS590-512W2E	MSS590-012W2E	42,150	Ⓢ	90	単相220	50 90~1400	730	260	540	1.4	253	MSP-2W	
			60 90~1600			1.3				236			
					単相230	50 90~1400	730	260	540	1.4	258	MSP-2W	
					60 90~1600	1.4				258			

Ⓢ:インピーダンスプロテクトされています。Ⓢ:サーマルプロテクトを内蔵しています。

## ギヤヘッド取付時の可変速度範囲 ●MSS003タイプ

減速比	3	3.6	5	6	7.5	9	12.5	15	18	25	30	36	50	60	75	90	100	120	150	180	
高速	50Hz	932	776	560	466	372	310	224	186	154	112	92	76	56	46	36	30	28	22	18	14
	60Hz	1132	944	680	566	452	376	272	226	188	136	112	94	68	56	44	36	34	28	22	18
低速		60	50	36	30	24	20	14.4	12	10	7.2	6	5	3.6	3	2.4	2	1.8	1.5	1.2	1

## ●MSS206、MSS315、MSS425、MSS540、MSS560、MSS590タイプ

減速比	3	3.6	5	6	7.5	9	12.5	15	18	25	30	36	50	60	75	90	100	120	150	180	
高速	50Hz	466	388	280	233	186	155	112	93	77	56	46	38	28	23	18	15	14	11	9	7
	60Hz	533	444	320	266	213	177	128	106	88	64	53	44	32	26	21	17	16	13	10	8.8
低速		30	25	18	15	12	10	7.2	6	5	3.6	3	2.5	1.8	1.5	1.2	1	0.9	0.75	0.6	0.5



空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境