



# 軸穴加工付スプロケットホイール

DKSチェーン歯車工業

204651

## FBN60型軸穴加工付スプロケットホイール(新JISキー溝対応)



形番	穴 D キー溝 押ねじ	18 6×2.8 2-M6	19 6×2.8 2-M6	20 6×2.8 2-M6	22 6×2.8 2-M6	24 8×3.3 2-M8	25 8×3.3 2-M8	28 8×3.3 2-M8	30 8×3.3 2-M8	32 10×3.3 2-M8	35 10×3.3 2-M8
FBN60B10			1,660	1,660	1,660	1,660	1,660	1,660	1,660		
FBN60B11			1,660	1,660	1,660	1,660	1,660	1,660	1,660	1,750	
FBN60B12			1,660	1,660	1,660	1,660	1,660	1,660	1,660	1,750	1,750
FBN60B13			1,750	1,750	1,750	1,750	1,750	1,750	1,750	1,840	1,840
FBN60B14			1,800	1,800	1,800	1,800	1,800	1,800	1,800	1,890	1,890
FBN60B15	1,930		1,930	1,930	1,930	1,930	1,930	1,930	1,930	2,020	2,020
FBN60B16			2,020	2,020	2,020	2,020	2,020	2,020	2,020	2,110	2,110
FBN60B17			2,110	2,110	2,110	2,110	2,110	2,110	2,110	2,240	2,240
FBN60B18			2,420	2,420	2,420	2,420	2,420	2,420	2,420	2,510	2,510
FBN60B19			2,550	2,550	2,550	2,550	2,550	2,550	2,550	2,620	2,620
FBN60B20			2,740	2,740	2,740	2,740	2,740	2,740	2,740	2,800	2,800
FBN60B21				2,850	2,850	2,850	2,850	2,850	2,850	2,900	2,900
FBN60B22				3,040	3,040	3,040	3,040	3,040	3,040	3,040	3,040
FBN60B23				3,130	3,130	3,130	3,130	3,130	3,130	3,200	3,200
FBN60B24				3,260	3,260	3,260	3,260	3,260	3,260	3,260	3,260
FBN60B25				3,360	3,360	3,360	3,360	3,360	3,360	3,360	3,360
FBN60B26				3,450	3,450	3,450	3,450	3,450	3,450	3,450	3,450
FBN60B27				3,600	3,600	3,600	3,600	3,600	3,600	3,600	3,600
FBN60B28					3,750	3,750	3,750	3,750	3,750	3,750	3,750
FBN60B29											
FBN60B30					4,000	4,000	4,000	4,000	4,000	4,000	4,000

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品、丸穴加工対応品も即納です。ご用命願います。

●形番の表示

FBN 60 B 20 - D20

FBN : 新JISキー溝対応  
チェーンNo. ボス形状  
歯数 軸穴径

●材質 : S35C歯先高周波焼入

軸穴寸法表

軸穴径 D	キー溝 b × t <sub>2</sub>	タップ
18H7	6 × 2.8	2-M6
19H7	6 × 2.8	2-M6
20H7	6 × 2.8	2-M6
22H7	6 × 2.8	2-M6
24H7	8 × 3.3	2-M8
25H7	8 × 3.3	2-M8
28H7	8 × 3.3	2-M8
30H7	8 × 3.3	2-M8
32H7	10 × 3.3	2-M8
35H7	10 × 3.3	2-M8
38H7	10 × 3.3	2-M8
40H7	12 × 3.3	2-M8
42H7	12 × 3.3	2-M8
45H7	14 × 3.8	2-M10
48H7	14 × 3.8	2-M10
50H7	14 × 3.8	2-M10
55H7	16 × 4.3	2-M12

形番	穴 D キー溝 押ねじ	38 10×3.3 2-M8	40 12×3.3 2-M8	42 12×3.3 2-M8	45 14×3.8 2-M10	48 14×3.8 2-M10	50 14×3.8 2-M10	55 16×4.3 2-M12
FBN60B10								
FBN60B11								
FBN60B12								
FBN60B13		1,840	1,840					
FBN60B14		1,890	2,020					
FBN60B15		2,020	2,020	2,200	2,200			
FBN60B16		2,110	2,110	2,240	2,240	2,240	2,240	
FBN60B17		2,240	2,240	2,380	2,380	2,380	2,380	
FBN60B18		2,510	2,510	2,510	2,510	2,780	2,780	2,780
FBN60B19		2,620	2,620	2,620	2,620	2,920	2,920	2,920
FBN60B20		2,800	2,800	2,900	2,900	2,900	2,900	2,900
FBN60B21		2,900	2,900	3,050	3,050	3,050	3,050	3,050
FBN60B22		3,040	3,040	3,140	3,140	3,140	3,140	3,590
FBN60B23		3,200	3,200	3,260	3,260	3,260	3,260	3,260
FBN60B24		3,260	3,260	3,340	3,340	3,340	3,340	3,810
FBN60B25		3,360	3,360	3,440	3,440	3,440	3,440	3,790
FBN60B26		3,450	3,450	3,530	3,530	3,530	3,530	3,950
FBN60B27		3,600	3,600	3,700	3,700	3,700	3,700	
FBN60B28		3,750	3,750	3,850	3,850	3,850	3,850	
FBN60B29								
FBN60B30		4,000	4,000	4,240	4,240	4,240	4,240	

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品、丸穴加工対応品も即納です。ご用命願います。

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境

