



## FBN80型軸穴加工付スプロケットホイール(新JISキー溝対応)



形番	穴 D	24	25	28	30	32	35	38	40	42	45
	キー溝	8×3.3	8×3.3	8×3.3	8×3.3	10×3.3	10×3.3	10×3.3	12×3.3	12×3.3	14×3.8
	押ねじ	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M10
FBN80B10			2,560	2,560	2,560	2,560					
FBN80B11			2,510	2,510	2,510	2,510	2,510	2,510			
FBN80B12			2,420	2,420	2,420	2,420	2,560	2,560	2,560	2,560	2,560
FBN80B13			2,560	2,560	2,560	2,560	2,560	2,560	2,560	2,870	2,870
FBN80B14			2,750	2,750	2,750	2,750	2,750	2,750	2,750	2,960	2,960
FBN80B15			3,110	3,110	3,110	3,110	3,110	3,110	3,110	3,320	3,320
FBN80B16		3,180	3,180	3,180	3,180	3,180	3,180	3,180	3,180	3,400	3,400
FBN80B17			3,610	3,610	3,610	3,610	3,610	3,610	3,610	3,720	3,720
FBN80B18			3,780	3,780	3,780	3,780	3,780	3,780	3,780	3,780	3,920
FBN80B19			3,940	3,940	3,940	3,940	3,940	3,940	3,940	4,020	4,020
FBN80B20			4,220	4,220	4,220	4,220	4,220	4,220	4,220	4,220	4,380
FBN80B21			4,660	4,660	4,660	4,660	4,660	4,660	4,660	4,660	4,660

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品。丸穴加工対応品も即納です。ご用命願います。

● 形番の表示

FBN80B20-D20

FBN: 新JISキー溝対応  
チェーンNo. ボス形状  
歯数 軸穴径

● 材質S35C歯先高周波焼入

形番	穴 D	48	50	55	60
	キー溝	14×3.8	14×3.8	16×4.3	18×4.4
	押ねじ	2-M10	2-M10	2-M12	2-M12
FBN80B10					
FBN80B11					
FBN80B12					
FBN80B13		2,870	2,870		
FBN80B14		2,960	2,960		
FBN80B15		3,320	3,320	3,500	3,500
FBN80B16		3,400	3,400	3,680	3,680
FBN80B17		3,720	3,720	3,800	3,800
FBN80B18		3,920	3,920	4,130	4,130
FBN80B19		4,020	4,020	4,310	4,310
FBN80B20		4,380	4,380	4,480	4,480
FBN80B21		4,660	4,660	4,720	4,720

軸穴寸法表

軸穴径 D	キー溝 b×t <sub>2</sub>	タップ
22H7	6×2.8	2-M6
24H7	8×3.3	2-M8
25H7	8×3.3	2-M8
28H7	8×3.3	2-M8
30H7	8×3.3	2-M8
32H7	10×3.3	2-M8
35H7	10×3.3	2-M8
38H7	10×3.3	2-M8
40H7	12×3.3	2-M8
42H7	12×3.3	2-M8
45H7	14×3.8	2-M10
48H7	14×3.8	2-M10
50H7	14×3.8	2-M10
55H7	16×4.3	2-M12
56H7	16×4.3	2-M12
60H7	18×4.4	2-M12

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品。丸穴加工対応品も即納です。ご用命願います。