



# 軸穴加工付スプロケットホイール

DKSチェーン歯車工業

204651

## FBN100型軸穴加工付スプロケットホイール(新JISキー溝対応)



形番	穴 D	25	28	30	32	35	38	40	42	45	48
	キー溝	8×3.3	8×3.3	8×3.3	10×3.3	10×3.3	10×3.3	12×3.3	12×3.3	14×3.8	14×3.8
	押ねじ	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M8	2-M10	2-M10
FBN100B10		4,890	4,890	4,890	5,070	5,070	5,070	5,070	5,070		
FBN100B11		4,890	4,890	4,890	5,070	5,070	5,070	5,070	5,070	5,070	5,070
FBN100B12		4,890	4,890	4,890	5,070	5,070	5,070	5,070	5,070	5,070	5,070
FBN100B13		5,340	5,340	5,340	5,520	5,520	5,520	5,520	5,520	5,520	5,520
FBN100B14		5,700	5,700	5,700	5,700	5,700	5,700	5,700	5,970	5,970	5,970
FBN100B15					6,330	6,330	6,330	6,330	6,330	6,330	6,330
FBN100B16							6,780			6,780	
FBN100B17							7,330			7,330	
FBN100B18							7,690			7,690	
FBN100B19							8,050			8,050	
FBN100B20							8,500			8,500	
FBN100B21										9,040	

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品、丸穴加工対応品も即納です。ご用命願います。

●形番の表示

FBN100B20-D20

FBN: 新JISキー溝対応  
チェーンNo. ボス形状  
歯数 軸穴径

●材質: S35C歯先高周波焼入

形番	穴 D	50	55	60
	キー溝	14×3.8	16×4.3	18×4.4
	押ねじ	2-M10	2-M12	2-M12
FBN100B10				
FBN100B11		5,070		
FBN100B12		5,070	5,070	
FBN100B13		5,520	5,520	
FBN100B14		5,970	5,970	5,970
FBN100B15		6,330	6,970	6,970
FBN100B16		6,780	7,330	7,330
FBN100B17		7,330		7,870
FBN100B18		7,690		8,230
FBN100B19		8,050		8,590
FBN100B20		8,500		9,140
FBN100B21		9,040		9,500

軸穴寸法表

軸穴径 D	キー溝 b×t2	タップ
22H7	6×2.8	2-M6
24H7	8×3.3	2-M8
25H7	8×3.3	2-M8
28H7	8×3.3	2-M8
30H7	8×3.3	2-M8
32H7	10×3.3	2-M8
35H7	10×3.3	2-M8
38H7	10×3.3	2-M8
40H7	12×3.3	2-M8
42H7	12×3.3	2-M8
45H7	14×3.8	2-M10
48H7	14×3.8	2-M10
50H7	14×3.8	2-M10
55H7	16×4.3	2-M12
60H7	18×4.4	2-M12
65H7	18×4.4	2-M12
70H7	20×4.9	2-M12

ボス径・ボス幅はB型と同じです。旧JISキー溝対応品、丸穴加工対応品も即納です。ご用命願います。



空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境