



A型



B型



KSSB型

●形式記号の組合せ
SSB 10 12
歯数

製品形式

SSB	S45Cボス付
SSA	S45Cボスナシ
SNB	キャストナイロンボス付
SNA	キャストナイロンボスナシ
SUB	SUS303ボス付
SUA	SUS303ボスナシ

モジュールピッチ (MP)

07	0.75	20	2.0	30	3.0
10	1.0	25	2.5	40	4.0

MP3.0スパーギヤ価格

共通寸法

単位: mm

形式	S45C		キャストナイロン		SUS303		S45C孔加工付					
	ボス付	ボス無	ボス付	ボス無	ボス付	ボス無	孔寸法		孔寸法		孔寸法	
	SSB	SSA	SNB	SNA	SUB	SUA	KSSB	孔径	KSSB	孔径	KSSB	孔径
3012	970	980	1,680	2,970	4,550	3,950	1,420	15K				
3014	1,110	1,060	1,850	3,170	4,550	4,240						
3015	1,190	1,120	2,120	3,370	4,930	4,490	1,720	15K	1,770	18K	1,850	20K
3016	1,200	1,210	2,140	3,610	4,990	4,810	1,800	15K	1,850	18K	1,940	20K
3017	1,210	1,270	2,700	3,810	5,750	5,060						
3018	1,350	1,330	2,700	3,990	6,430	5,310	2,070	18K	2,150	20K	2,210	25K
3019	1,650	1,400	2,900	4,300	6,800	5,800						
3020	1,760	1,400	2,900	4,300	7,240	5,800	2,300	20K	2,370	25K	2,370	30K
3021	1,920	1,570	3,540	4,300	7,420	6,080						
3022	2,030	1,600	3,540	4,300	7,800	6,370	2,520	20K	2,590	25K	2,590	30K
3023	2,180	1,670	3,800	4,350	8,320	6,660						
3024	2,220	1,680	3,800	4,350	8,800	6,950	2,700	20K	2,750	25K	2,750	30K
3025	2,390	1,830	4,080	4,350	9,800	7,600	2,930	20K	2,940	25K	2,940	30K
3026	2,570	1,990	4,100	4,350	10,660	7,810	3,060	20K	3,070	25K	3,070	30K
3027	2,750	2,060	4,550	4,400	10,660	8,250						
3028	2,790	2,190	4,600	4,400	11,660	8,720	3,270	20K	3,360	25K	3,360	30K
3029	2,830	2,220	5,290	4,400	11,540	9,010						
3030	2,970	2,360	5,300	4,400	12,500	9,160	3,550	25K	3,550	30K	3,760	35K
3032	3,300	2,680	6,490	4,410	10,000	4,190	4,190	25K	4,190	30K	4,350	35K
3034	3,780	3,030	6,500	5,100	11,440							
3035	3,810	3,090	8,750	5,160	11,800							
3036	3,830	3,120	8,750	5,180	12,000	4,850	4,850	25K	4,850	30K	5,000	35K
3038	4,390	3,500	8,750	6,000	13,440							
3040	4,440	3,540	8,750	6,010	14,490	5,540	5,540	30K	5,700	35K	5,800	40K
3042	4,870	4,400	7,200		16,200	6,120	6,120	30K	6,280	35K	6,380	40K
3044	5,420	4,400	7,200		16,800							
3045	5,450	4,410	7,270		18,000	6,850	6,850	30K	7,060	35K	7,140	40K
3046	5,520	5,030	7,700		19,080							
3048	6,220	5,050	7,750		20,400	7,660	7,660	30K	7,870	35K	7,940	40K
3050	6,440	5,180	8,130		21,590	8,170	8,170	30K	8,330	35K	8,440	40K
3052	6,960	6,030										
3054	7,630	6,050										
3055	7,690	6,080										
3056	8,140	6,380					9,230	35K	9,410	40K	9,870	45K
3058	8,540	6,800										
3060	8,620	6,840					10,920	35K	10,990	40K	11,360	45K
3062	9,830	8,300										
3064	11,030	8,440										
3065	11,140	9,000										
3066	11,880	9,100										
3068	11,880	9,200										
3070	12,000	9,300										
3072	13,030	11,770										
3075	14,140	11,880										
3076	14,400	11,900										
3080	14,410	11,980										
3084		19,800										
3085	21,720	21,450										
3088		24,750										
3090	23,280	25,960										
3095	28,320	25,960										
30100	23,600	25,960										
30120												

歯数	主要寸法					
	ピッチ円 P.C.D	外径 D	歯幅 W	穴径 d _{h7}	ボス径 B	ボス長 BL
12	36	42	30	15	27	18
14	42	48	30	15	32	18
15	45	51	30	15	35	18
16	48	54	30	16	40	18
17	51	57	30	16	40	18
18	54	60	30	16	44	18
19	57	63	30	16	46	18
20	60	66	30	18	50	18
21	63	69	30	18	52	18
22	66	72	30	18	54	18
23	69	75	30	18	56	18
24	72	78	30	18	58	18
25	75	81	30	18	60	18
26	78	84	30	20	65	18
27	81	87	30	20	65	18
28	84	90	30	20	70	18
29	87	93	30	20	75	18
30	90	96	30	20	75	18
32	96	102	30	20	75	18
34	102	108	30	20	80	18
35	105	111	30	22	80	18
36	108	114	30	22	80	18
38	114	120	30	22	80	18
40	120	126	30	22	85	18
42	126	132	30	22	85	18
44	132	138	30	22	85	18
45	135	141	30	22	85	18
46	138	144	30	22	85	18
48	144	150	30	22	85	18
50	150	156	30	22	85	18
52	156	162	30	22	85	18
54	162	168	30	22	90	18
55	165	171	30	22	90	18
56	168	174	30	25	95	18
58	174	180	30	25	95	18
60	180	186	30	25	100	18
62	186	192	30	25	100	18
64	192	198	30	25	110	18
65	195	201	30	25	110	18
66	198	204	30	25	110	18
68	204	210	30	25	110	18
70	210	216	30	25	110	18
72	216	222	30	25	120	18
75	225	231	30	25	120	18
76	228	234	30	25	120	18
80	240	246	30	25	130	18
84	252	258	30	25	130	18
85	255	261	30	25	130	18
88	264	270	30	25	130	18
90	270	276	30	25	130	18
95	285	291	30	25	130	18
100	300	306	30	28	140	18
120	360	366	30	28		

KSSB孔加工付歯車にはすべて押しねじが付属しています。

