



A型



B型



KSSB型

●形式記号の組合せ
SSB 10 12
歯数

製品形式

SSB	S45Cボス付
SSA	S45Cボスナシ
SNB	キャストナイロンボス付
SNA	キャストナイロンボスナシ
SUB	SUS303ボス付
SUA	SUS303ボスナシ

モジュールピッチ (MP)

07	0.75	20	2.0	30	3.0
10	1.0	25	2.5	40	4.0

MP4.0スパーギヤ価格

共通寸法

単位: mm

形式	S45C		キャストナイロン		SUS303		S45C孔加工付			歯数	主要寸法								
	ボス付	ボス無	ボス付	ボス無	ボス付	ボス無	孔寸法				ピッチ円	外径	歯幅	穴径	ボス径	ボス長			
	SSB	SSA	SNB	SNA	SUB	SUA	KSSB	孔径	KSSB	孔径	KSSB	孔径	P.C.D.	D	W	d ₁₇	B	BL	
4012	1,680	1,540		4,640			2,350	18K	2,420	20K		12	48	56	40	18	36	21	
4014	2,010	1,790		5,380								14	56	64	40	18	44	21	
4015	2,080	1,930	6,970	5,750	8,920		2,740	18K	2,810	20K	2,880	25K	15	60	68	40	18	48	21
4016	2,300	2,050		6,140			3,040	20K	3,100	25K	3,100	30K	16	64	72	40	20	52	21
4017	2,530	2,180		6,510									17	68	76	40	20	56	21
4018	2,770	2,290		6,900			3,600	20K	3,610	25K	3,610	30K	18	72	80	40	20	60	21
4019	2,980	2,430		7,280									19	76	84	40	20	63	21
4020	3,240	2,750	9,680	7,660	13,720		3,770	20K	3,780	25K	3,780	30K	20	80	88	40	22	66	21
4021	3,430	2,760		8,310									21	84	92	40	22	70	21
4022	3,670	2,980		8,930			4,240	20K	4,310	25K	4,310	30K	22	88	96	40	22	72	21
4023	4,210	3,360		9,590									23	92	100	40	22	75	21
4024	4,230	3,530		10,230			4,830	20K	4,890	25K	4,890	30K	24	96	104	40	22	78	21
4025	4,810	3,570	14,300	10,400	19,800		5,370	25K	5,370	30K	5,370	35K	25	100	108	40	25	84	21
4026	4,890	3,920		10,810			5,540	25K	5,540	30K	5,710	35K	26	104	112	40	25	87	21
4027	4,960	3,980		11,550									27	108	116	40	25	90	21
4028	5,530	4,310		12,430			6,330	25K	6,390	30K	6,390	35K	28	112	120	40	25	95	21
4029	5,730	4,420		12,540									29	116	124	40	25	95	21
4030	6,070	4,420	17,710	12,870	25,970		6,980	30K	7,070	35K	7,150	40K	30	120	128	40	25	100	21
4032	6,160	4,890					7,320	30K	7,420	35K	7,500	40K	32	128	136	40	25	100	21
4034	6,600	5,830											34	136	144	40	25	100	21
4035	7,420	6,120											35	140	148	40	28	100	21
4036	7,470	6,210					9,220	30K	9,310	35K	9,390	40K	36	144	152	40	28	100	21
4038	8,420	7,400											38	152	160	40	28	100	21
4040	9,270	7,410					11,190	35K	11,270	40K	11,630	45K	40	160	168	40	28	100	21
4042	9,410	8,160					11,630	35K	11,710	40K	12,070	45K	42	168	176	40	28	100	21
4044	10,310	9,010											44	176	184	40	28	100	21
4045	11,430	9,170					13,760	35K	13,840	40K	14,200	45K	45	180	188	40	28	100	21
4046	11,580	10,300											46	184	192	40	28	100	21
4048	13,030	10,370					15,470	35K	15,620	40K	16,120	45K	48	192	200	40	28	110	21
4050	13,330	11,220					16,920	35K	16,940	40K	17,490	45K	50	200	208	40	28	110	21
4052	14,320	13,110											52	208	216	40	28	110	21
4054	15,570	13,200											54	216	224	40	28	110	21
4055	16,910	13,240											55	220	228	40	28	120	21
4056	17,380	14,190											56	224	232	40	30	120	21
4058	18,450	15,490											58	232	240	40	30	120	21
4060	19,220	15,960											60	240	248	40	30	130	21
4062	20,480	19,580											62	248	256	40	30	130	21
4064	22,110	20,330											64	256	264	40	30	140	21
4065	23,770	20,940											65	260	268	40	30	140	21
4066	25,300	22,550											66	264	272	40	30	140	21
4068	25,690	23,430											68	272	280	40	30	150	21
4070	26,280	25,080											70	280	288	40	30	150	21
4072	32,800	27,720											72	288	296	40	30	150	21
4075	32,800	29,160											75	300	308	40	30	150	21
4076													76	304	312	40	30	150	21
4080	32,800	34,680											80	320	328	40	30	150	21
4084													84	336	344	40	30	150	21
4085	69,740	53,680											85	340	348	40	32	150	21
4088													88	352	360	40	32		
4090													90	360	368	40	32		
4095													95	380	388	40	32		
40100													100	400	408	40	35		
41200													120	480	488	40	35		

KSSB孔加工付歯車にはすべて押しねじが付属しています。