


A型



B型

- 形式記号の組合せ
SSB 10 12
歯数

製品形式

SSB	S45Cボス付
SSA	S45Cボスナシ
SNB	キャストナイロンボス付
SNA	キャストナイロンボスナシ
SUB	SUS303ボス付
SUA	SUS303ボスナシ

モジュールピッチ (MP)

07	0.75	20	2.0	30	3.0
10	1.0	25	2.5	40	4.0

MP6.0スーパーギヤ価格

共通寸法

単位: mm

形式	S45C		キャストナイロン		SUS303		歯数	主要寸法					
	ボス付 SSB	ボス無 SSA	ボス付 SNB	ボス無 SNA	ボス付 SUB	ボス無 SUA		ピッチ円 P.C.D	外径 D	歯幅 W	穴径 d _{HT}	ボス径 B	ボス長 BL
6012	4,450	4,390					12	72	84	60	25	54	28
6014	5,220	4,730					14	84	96	60	25	66	28
6015	5,970	4,730	18,040		27,500		15	90	102	60	25	72	28
6016	6,740	5,870					16	96	108	60	28	78	28
6017	6,840	5,870					17	102	114	60	28	84	28
6018	7,680	6,060					18	108	120	60	28	90	28
6019	7,840	6,260					19	114	126	60	28	96	28
6020	8,770	6,890	25,960		37,560		20	120	132	60	28	100	28
6021	9,830	7,760					21	126	138	60	30	105	28
6022	9,970	7,880					22	132	144	60	30	110	28
6023	11,160	8,770					23	138	150	60	30	115	28
6024	11,370	8,860					24	144	156	60	30	120	28
6025	12,460	9,790	37,510				25	150	162	60	30	120	28
6026	13,660	11,440					26	156	168	60	32	120	28
6027	13,850	11,440					27	162	174	60	32	130	28
6028	15,420	11,930					28	168	180	60	32	130	28
6029	18,340	12,670					29	174	186	60	32	130	28
6030	18,500	13,090					30	180	192	60	32	130	28
6032	19,240	14,830					32	192	204	60	32	130	28
6034	20,890	18,810					34	204	216	60	32	130	28
6035	23,700	18,810					35	210	222	60	32	130	28
6036	25,200	19,200					36	216	228	60	32	130	28
6038	26,700	22,880					38	228	240	60	32	130	28
6040	30,640	24,100					40	240	252	60	35	140	28
6042	32,330	29,480					42	252	264	60	35	140	28
6044	36,120	29,480					44	264	276	60	35	140	28
6045	36,560	30,140					45	270	282	60	35	140	28
6046	38,690	37,480					46	276	288	60	35	140	28
6048	41,950	37,660					48	288	300	60	35	150	28
6050	44,130	40,320					50	300	312	60	35	150	28
6052							52	312	324	60	35		
6054							54	324	336	60	35		
6055							55	330	342	60	35		
6056							56	336	348	60	35		
6058							58	348	360	60	35		
6060							60	360	372	60	35		
6062							62	372	384	60	35		
6064							64	384	396	60	35		
6065							65	390	402	60	35		
6066							66	396	408	60	35		
6068							68	408	420	60	35		
6070							70	420	432	60	38		
6072							72	432	444	60	38		
6075							75	450	462	60	38		
6076							76	456	468	60	38		
6080							80	480	492	60	38		
							84						
							85						
							88						
							90						
							95						
							100						
							120						

上記以外のご希望の材質又は特殊寸法も対応致します。