



ウォームギヤ・ウォームホイール



- ・ウォームギヤは1条で進み角が4°以下の場合セルフロック作用が働きます。
- ・静粛な回転が得られ、低騒音で運転可能です。

ウォームギヤ 圧力角:20° 材質:S45C 単位:mm

形式	価格	ピッチボス径 全長			形式	価格	ピッチボス径 全長		
		P.C.D	B	L			P.C.D	B	L
WS10S	580	16	18	32	WS40S	4,680	57	45	95
10D	590				40D	4,830			
WS15S	900	25	20	40	WS50S	7,350	65	52	120
15D	940				50D	7,450			
WS20S	960	31	25	52	WS60S	9,600	78	62	150
20D	1,030				60D	9,780			
WS25S	1,680	37	30	63	WS80S	19,030	94	72	200
25D	1,780				80D	20,570			
WS30S	2,090	44	36	75	WS100S	34,980	110	82	250
30D	2,160				100D	37,510			

HF型ウォームギヤ 圧力角:20° 材質:FC20

単位:mm

形式	価格		減速比	モジュール	歯幅	中心距離	外径	ボス径	ボス長	形式	価格		減速比	モジュール	歯幅	中心距離	外径	ボス径	ボス長
	ホイールのみ	組価									ホイールのみ	組価							
HF 1020D	560	1,150	1/10	1.0	10	18	22	16	10	HF 4020D	3,070	7,900	1/10	4.0	35	68.5	88	60	17
1030D	830	1,420	1/15		10	23	32	20	10	4030D	4,200	9,030	1/15		35	88.5	128	60	17
1020S	560	1,140	1/20		10	18	22	16	10	4020S	3,070	7,750	1/20		35	68.5	88	60	17
1030S	830	1,410	1/30		10	23	32	20	10	4030S	4,200	8,880	1/30		35	88.5	128	60	17
1040S	1,000	1,580	1/40		10	28	42	26	10	4040S	5,670	10,350	1/40		35	108.5	168	70	17
1050S	1,100	1,680	1/50		10	33	52	30	10	4050S	7,320	12,000	1/50		35	128.5	208	70	17
1060S	1,140	1,720	1/60		10	38	62	30	10	4060S	9,950	14,630	1/60		35	148.5	248	80	17
HF 1520D	860	1,800	1/10	1.5	12	27.5	33	22	10	HF 5020D	5,830	13,280	1/10	5.0	45	82.5	110	75	20
1530D	900	1,840	1/15		12	35	48	30	10	5030D	8,040	15,490	1/15		45	107.5	160	75	20
1520S	860	1,760	1/20		12	27.5	33	22	10	5020S	5,830	13,180	1/20		45	82.5	110	75	20
1530S	930	1,830	1/30		12	35	48	30	10	5030S	8,040	15,390	1/30		45	107.5	160	75	20
1540S	1,220	2,120	1/40		12	42.5	63	30	10	5040S	10,910	18,260	1/40		45	132.5	210	90	20
1550S	1,580	2,480	1/50		14	50	78	40	10	5050S	13,190	20,540	1/50		45	157.5	260	90	20
1560S	1,860	2,760	1/60		14	57.5	93	40	10	5060S	18,140	25,490	1/60		45	182.5	310	100	20
HF 2020D	1,020	2,050	1/10	2.0	22	35.5	44	33	13	HF 6020D	8,550	18,330	1/10	6.0	52	99	132	100	20
2030D	1,440	2,470	1/15		22	45.5	64	40	13	6030D	11,420	21,200	1/15		52	129	192	100	20
2020S	1,020	1,980	1/20		22	55.5	44	33	13	6020S	8,550	18,150	1/20		52	99	132	100	20
2030S	1,440	2,400	1/30		22	45.5	64	40	13	6030S	11,420	21,020	1/30		52	129	192	100	20
2040S	2,000	2,960	1/40		22	55.5	84	45	13	6040S	15,490	25,090	1/40		52	159	252	100	20
2050S	2,380	3,340	1/50		22	65.5	104	48	13	6050S	22,110	31,710	1/50		52	189	312	100	20
2060S	2,880	3,840	1/60		22	75.5	124	50	13	6060S	29,120	38,720	1/60		52	219	372	120	20
HF 2520D	1,240	3,020	1/10	2.5	22	43.5	55	35	14	HF 8020D	24,970	45,540	1/10	8.0	60	127	176	125	25
2530D	1,760	3,540	1/15		22	56	80	40	14	8030D	28,600	49,170	1/15		60	167	256	125	25
2520S	1,240	2,920	1/20		22	43.5	55	35	14	8020S	24,970	44,000	1/20		60	127	176	125	25
2530S	1,760	3,440	1/30		22	56	80	40	14	8030S	28,600	47,630	1/30		60	167	256	125	25
2540S	2,390	4,070	1/40		22	68.5	105	45	14	8040S	42,070	61,100	1/40		60	207	336	125	25
2550S	2,970	4,650	1/50		22	65.5	130	50	14	8050S	49,830	68,860	1/50		60	247	416	125	25
2560S	3,710	5,390	1/60		22	93.5	155	55	14	8060S	66,770	85,800	1/60		60	287	496	140	25
HF 3020D	1,810	3,970	1/10	3.0	28	52	66	50	15	HF 10020D	64,900	102,410	1/10	10.0	72	155	220	140	28
3030D	2,950	5,110	1/15		28	67	96	55	15	10030D	74,690	112,200	1/15		72	205	320	140	28
3020S	1,810	3,900	1/20		28	52	66	50	15	10020S	64,900	99,880	1/20		72	155	220	140	28
3030S	2,950	5,040	1/30		28	67	96	55	15	10030S	74,690	109,670	1/30		72	205	320	140	28
3040S	3,530	5,620	1/40		30	82	126	55	15	10040S	97,570	132,550	1/40		72	255	420	140	28
3050S	4,430	6,520	1/50		30	97	156	63	15	10050S	138,600	173,580	1/50		72	305	520	160	28
3060S	5,550	7,640	1/60		30	112	186	70	15	10060S	167,200	202,180	1/60		72	355	620	160	28

