

スチール製ローラコンベヤ

(株)マキテック

311561

R-6023スチール製ローラコンベヤ



フレーム寸法L×K×(mm)	□ 90 × 30 × 3.2
コンベヤ機高 H (mm)	102
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d (mm)	60.5×2.3× 15 ヌキ付
ローラ巾製作範囲	100~1,000 50とび
W (mm)フリーサイズ	特殊仕様となります。
ベアリング	削り出しベアリング
軸 (mm)	15パイプ 半月

ローラ巾 W (mm)	100	200	300	400	500	600	700	800	900	1,000
機 巾W + 75 (mm)	175	275	375	475	575	675	775	875	975	1,075
ローラ強度 (kg)	376	345	293	250	200	158	143	117	100	93
コンベヤ重量目安	75P 45.4	63.4	81.4	99.4	117.4	135.4	153.4	171.4	189.4	207.4
3,000L (kg)	100P 39.8	53.4	67.0	80.6	94.2	107.8	121.4	135.0	148.6	162.2
ローラ軸付重量目安 (g)	0.6	1.0	1.4	1.9	2.3	2.8	3.2	3.6	4.1	4.5

R-6023形価格

ローラ間隔	機長	100W	150W	200W	250W	300W	350W	400W	500W	600W	800W	1,000W
75P	3,000L	68,500	74,700	81,100	87,500	93,900	100,300	106,800	119,500	132,100	158,100	188,000
	2,000L	43,800	48,000	51,900	56,100	60,400	64,600	68,600	77,200	86,000	104,000	124,800
	1,000L	23,900	25,900	27,900	30,200	32,100	34,200	36,300	40,600	45,000	53,900	64,700
	内900R × 90°	63,400	67,700	70,700	75,200	78,300	82,700	85,900	93,700	101,700	118,000	141,500
100P	3,000L	56,900	61,800	66,300	71,200	75,600	80,800	85,500	95,400	105,300	124,800	147,900
	2,000L	36,400	39,800	42,900	46,100	49,200	52,500	55,800	62,400	69,000	83,100	99,700
	1,000L	20,200	21,800	23,500	24,900	26,500	28,300	30,100	33,200	36,600	43,700	52,500
	内900R × 90°	57,100	60,600	62,800	66,400	68,800	72,400	74,800	80,800	87,200	99,900	120,000
150P	3,000L	45,800	49,200	52,800	56,100	59,300	63,000	66,500	73,700	81,100	95,900	113,700
	2,000L	28,400	30,400	32,400	34,400	36,600	38,700	40,800	45,000	49,300	58,400	70,000
	1,000L	16,000	17,000	18,000	19,100	20,200	21,300	22,200	24,500	26,600	31,300	37,600
	内900R × 90°	51,000	53,700	55,500	58,000	59,900	62,700	64,600	69,200	74,000	83,900	100,600
200P	3,000L	43,100	45,300	47,500	49,800	51,900	54,300	56,600	61,400	66,300	76,200	91,200
	2,000L	23,800	25,600	27,200	28,800	30,500	32,400	34,100	37,600	41,100	48,300	58,000
	1,000L	13,700	14,500	15,500	16,300	17,100	18,100	18,900	20,800	22,200	26,500	32,000
	内900R × 90°	49,200	50,000	51,400	52,900	53,700	55,100	55,900	58,100	60,600	65,400	78,400
ローラ単品	軸付	1,440	1,660	1,810	2,060	2,220	2,430	2,560	2,880	3,270	4,080	4,890
	軸なし	1,240	1,430	1,550	1,780	1,940	2,080	2,190	2,420	2,750	3,440	4,130

R-6038SBスチール製ローラコンベヤ



フレーム寸法L×K×(mm)	□ 90 × 30 × 4.5
コンベヤ機高 H (mm)	100
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d (mm)	60.5×3.8× 20
ローラ巾製作範囲	100~1000
W (mm)フリーサイズ	製作できます
ベアリング	規格相当
軸 (mm)	20丸棒 半月

ローラ巾 W (mm)	100	200	300	400	500	600	700	800	900	1000
機 巾W + 75 (mm)	175	275	375	475	575	675	775	875	975	1075
ローラ強度 (kg)	570	538	505	475	475	475	450	420	400	380
コンベヤ重量目安	75P 65	94.6	124.6	154.6	184.6	214.6	244.6	274.6	304.6	339.6
3,000L (kg)	100P 56	78.7	101.3	123.9	146.5	169.1	191.7	214.3	236.9	259.5
ローラ軸付重量目安 (kg)	0.9	1.6	2.3	3.1	3.8	4.6	5.3	6.0	6.8	7.5

R-6038SB形価格

ローラ間隔	機長	100W	200W	300W	400W	500W	600W	700W	800W	900W	1000W
75P	3,000L	111,600	125,900	140,200	155,000	170,000	185,300	200,700	216,600	237,200	257,800
	2,000L	73,300	83,700	94,500	105,600	116,700	128,200	139,800	151,600	166,700	181,800
	1,000L	38,400	43,700	49,200	54,900	60,600	66,500	72,500	78,600	86,600	94,200
	内900R × 90°	79,900	88,800	98,000	107,500	117,000	126,800	136,800	146,900	161,500	176,300
100P	3,000L	93,900	104,700	115,700	127,100	138,400	150,300	162,000	174,300	190,700	207,000
	2,000L	60,200	68,400	76,700	85,600	94,100	103,200	112,300	121,700	133,900	146,000
	1,000L	32,300	36,400	40,500	45,000	49,200	53,800	58,300	63,100	69,500	75,600
	内900R × 90°	68,700	76,300	83,500	91,000	98,900	106,500	114,500	122,700	135,000	147,300
150P	3,000L	71,700	79,900	88,500	97,600	106,200	115,100	123,700	132,500	144,800	156,900
	2,000L	45,300	51,200	57,200	63,300	69,600	75,800	82,300	88,900	97,700	106,300
	1,000L	24,700	27,700	31,000	34,500	37,700	41,500	44,800	48,300	53,200	57,900
	内900R × 90°	59,100	64,700	70,800	76,700	82,900	89,000	95,600	101,000	111,200	121,300
200P	3,000L	60,500	66,900	73,300	79,600	86,300	93,600	100,700	107,500	117,100	126,900
	2,000L	39,500	43,800	48,300	52,900	57,600	62,400	67,300	72,300	79,500	86,800
	1,000L	21,600	23,900	26,300	28,600	31,000	33,300	35,900	38,400	42,200	46,100
	内900R × 90°	54,400	59,200	64,200	69,200	74,200	79,300	84,600	89,900	99,000	108,000
ローラ単品	軸付	2,800	3,260	3,680	4,200	4,680	5,010	5,720	6,250	6,870	7,520
	軸なし	2,450	2,750	3,050	3,370	3,710	3,890	4,430	4,800	5,290	5,760

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機粉体

工場設備・環境