



215モータープーリ1.5kW(三相200V級)仕様および価格

型式	価格	出力		定格電流値 [A]		速度 [m/min]		定格トルク [N·m]		定格接線力 [N]		減速	
		[kW]	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	減速比	段数	
KMP-A153-4C-215-380-36AAA	91,000	1.5	6.6	6.0	35.9	43.3	228	189	2120	1758	1/26	2	
KMP-A153-4C-215-450-13AAA	128,000				13.2	15.9	587	486	5460	4520	1/74	3	
KMP-A153-4C-215-450-16AAA	128,000				15.5	18.7	500	414	4651	3851	1/61	3	
KMP-A153-4C-215-450-20AAA	128,000				19.9	24.0	389	322	3618	2995	1/49	3	
KMP-A153-4C-215-450-25AAA	128,000				25.2	30.4	306	254	2846	2362	1/39	3	
KMP-A153-4C-215-450-30AAA	128,000				29.0	35.0	266	220	2474	2046	1/33	3	
KMP-A153-4C-215-450-33AAA	125,000				33.4	40.3	245	203	2279	1888	1/29	2	
KMP-A153-4C-215-450-39AAA	105,000				39.7	47.9	206	171	1916	1590	1/25	2	
KMP-A153-4C-215-450-50AAA	130,000				47.1	56.8	174	144	1618	1339	1/20	2	

265モータープーリ1.5kW・2.2kW(三相200V級)仕様および価格

KMP-A153-6C-265-450-22AAA	156,000	1.1	6.0	5.2	23.0	27.6	323	269	2437	2030	1/35	2
KMP-A153-4C-265-450-34AAA	133,000				35.1	42.2	288	240	2173	1811	1/35	2
KMP-A153-4C-265-450-43AAA	133,000	1.5	6.8	6.0	44.8	53.9	225	187	1698	1411	1/27	2
KMP-A153-4C-265-500-18AAA	184,000				18.8	22.6	371	309	2800	2332	1/42	3
KMP-A153-4C-265-500-28AAA	175,000	1.5	7.1	6.2	28.7	34.5	332	276	2505	2083	1/42	3
KMP-A153-4C-265-500-42AAA	175,000				41.5	49.9	229	190	1728	1433	1/29	3
KMP-A153-4C-265-500-59AAA	175,000				59.2	71.2	161	133	1215	1003	1/20	3
KMP-A153-4C-265-500-67AAA	175,000				66.6	80.1	143	119	1079	898	1/18	3
KMP-A153-4C-265-500-96AAA	175,000				96.5	116.0	98	82	739	618	1/12	3
KMP-A223-6C-265-550-18AAA	214,000				1.7	9.2	8.0	18.9	22.5	573	479	4324
KMP-A223-4C-265-550-28AAA	210,000	28.6	34.5	488				405	3683	3056	1/42	3
KMP-A223-4C-265-550-33AAA	223,000	33.9	40.8	412				343	3109	2588	1/36	3
KMP-A223-4C-265-550-42AAA	210,000	41.4	49.9	337				280	2543	2113	1/29	3
KMP-A223-4C-265-550-47AAA	223,000	46.7	56.2	299				248	2256	1871	1/26	3
KMP-A223-4C-265-550-51AAA	223,000	50.5	60.8	277				230	2090	1735	1/24	3
KMP-A223-4C-265-550-59AAA	223,000	2.2	10.4	9.0	59.1	71.1	236	196	1781	1479	1/20	3
KMP-A223-4C-265-550-67AAA	223,000				66.5	80.0	210	174	1584	1313	1/18	3
KMP-A223-4C-265-550-96AAA	223,000				96.3	115.9	145	120	1094	905	1/12	3

318モータープーリ1.5kW・2.2kW・3.7kW(三相200V級)仕様および価格

KMP-A153-4C-318-500-33AAA	193,000	1.5	7.1	6.2	34.4	41.4	332	276	2088	1735	1/42	3
KMP-A153-4C-318-500-41AAA	193,000				40.7	49.0	280	233	1761	1465	1/36	3
KMP-A153-4C-318-500-50AAA	193,000				49.8	59.9	229	190	1440	1194	1/29	3
KMP-A223-6C-318-550-22AAA	224,000	1.7	9.2	8.0	22.6	27.0	573	479	3603	3012	1/42	3
KMP-A223-4C-318-550-33AAA	217,000				34.4	41.4	488	405	3069	2547	1/42	3
KMP-A223-4C-318-550-41AAA	217,000				40.6	48.9	412	343	2591	2157	1/36	3
KMP-A223-4C-318-550-50AAA	194,000	2.2	10.4	9.0	49.7	59.9	337	280	2119	1761	1/29	3
KMP-A223-4C-318-550-56AAA	238,000				56.0	67.4	299	248	1880	1559	1/26	3
KMP-A223-4C-318-550-71AAA	238,000				70.9	85.3	236	196	1484	1232	1/20	3
KMP-A373-4C-318-550-50AAA	245,000	3.7	14.5	14.0	52.1	62.7	541	450	3402	2830	1/27	2
KMP-A373-4C-318-550-67AAA	286,000				67.0	80.6	421	350	2647	2201	1/21	2
KMP-A373-4C-318-550-96AAA	306,000				96.6	116.2	292	243	1836	1528	1/15	2

注 すべてのシリーズに三相400V仕様、プーリストレーツ仕様が可能です。お問い合わせ願います。プーリ幅の延長も可能です。

特殊仕様モータープーリ

堅牢防水仕様



Wヘリカルゴムライニング

