

電動トリリ結合式 電気チェーンブロック

高頻度作業、電動トリリ、2速式、高速式、低速式また横行レールの回転半径が小さいトリリ等、種々組合せができます。作業に合った機種をご使用下さい。

DAM型(定速式)  
電動トリリ結合式



定格荷重0.25t ~ 10t

### DAM型(定速式)電気チェーンブロック仕様・価格

型式	価格	定格荷重 (ton)	標準揚程 (m)	押しボタンコード長さ (m)	電源コード	巻上モータ出力 (kW)	巻上速度 (m/分)		フック間最小距離 (mm)	自重 (kg)	
							50Hz	60Hz			
DAM-0.25	285,800	0.25	3	2.5 又は 5.5	標準 0.5m付	0.5	7.8	9.3	570	73	
	301,400		6				77				
DAM-0.49	316,500	0.49	3				0.9	7.4	8.7	580	75
	332,400		6				79				
DAM-0.5	316,500	0.5	3				0.9	7.3	8.6	580	75
	332,400		6				79				
DAM-0.9S	353,300	0.9	3				1.7	6.9	8.3	620	101
	371,000		6				106				
DAM-0.9W	341,300	0.9	3				0.9	3.7	4.4	740	92
	364,100		6				102				
DAM-1S	353,300	1	3				1.7	6.8	8.2	620	101
	371,000		6				106				
DAM-1W	341,300	1	3				0.9	3.6	4.3	740	92
	364,100		6				102				
DAM-1.5	446,600	1.5	3				3.4	8.7	10.3	780	192
	467,600		6				200				
DAM-2S	454,500	2	3				3.4	6.9	8.1	735	197
	477,000		6				206				
DAM-2W	424,300	2	3				1.7	3.4	4.1	795	124
	450,700		6				133				
DAM-2.5	529,600	2.5	4	3.4	5.5	6.5	750	192			
	544,600		6								
DAM-2.8	560,300	2.8	4	3.4	4.43	5.25	960	209			
	582,300		6								
DAM-3	560,300	3	4	3.4	4.35	5.15	960	209			
	582,300		6								
DAM-5	782,000	5	4	3.4	2.75	3.25	1050	246			
	806,000		6								
DAM-7.5	1,614,000	7.5	4	3.4	1.8	2.1	1205	480			
DAM-10	1,963,000	10	4	3.4×2	2.7	3.2	1185	619			

DBM型(2速式)  
電動トリリ結合式



定格荷重0.25t ~ 10t

### DBM型(2速式)電気チェーンブロック仕様・価格

型式	価格	定格荷重 (ton)	標準揚程 (m)	押しボタンコード長さ (m)	電源コード	巻上モータ出力 (kW)	巻上速度 (m/分)			フック間最小距離 (mm)	自重 (kg)
							1速:2速	1速:2速	1速:2速		
DBM-0.25	331,500	0.25	3	2.5 又は 5.5	標準 0.5m付	0.5 : 0.17	7.8 : 2.6	9.3 : 3.1	570	87	
	348,900		6				91				
DBM-0.49	377,900	0.49	3				0.9 : 0.3	7.4 : 2.5	8.7 : 2.8	580	91
	395,600		6				96				
DBM-0.5	377,900	0.5	3				0.9 : 0.3	7.3 : 2.4	8.6 : 2.8	580	91
	395,600		6				96				
DBM-0.9S	436,900	0.9	3				1.7 : 0.57	6.9 : 2.3	8.3 : 2.8	640	121
	456,400		6				126				
DBM-0.9W	421,900	0.9	3				0.9 : 0.3	3.7 : 1.2	4.4 : 1.5	740	111
	446,500		6				119				
DBM-1S	436,900	1	3				1.7 : 0.57	6.8 : 2.2	8.2 : 2.7	620	121
	456,400		6				126				
DBM-1W	421,900	1	3				0.9 : 0.3	3.6 : 1.2	4.3 : 1.4	740	111
	446,500		6				119				
DBM-1.5	532,300	1.5	3				3.4 : 1.14	8.7 : 2.9	10.3 : 3.4	780	213
	555,100		6				220				
DBM-2S	557,500	2	3				3.4 : 1.14	6.9 : 2.3	8.1 : 2.7	735	217
	581,800		6				227				
DBM-2W	519,500	2	3				1.7 : 0.57	3.4 : 1.1	4.1 : 1.3	795	144
	547,700		6				153				
DBM-2.5	640,000	2.5	4	3.4 : 1.14	5.5 : 1.8	6.5 : 2.1	750	209			
	656,200		6								
DBM-2.8	672,500	2.8	4	3.4 : 1.14	4.43 : 1.45	5.25 : 1.75	960	226			
	695,700		6								
DBM-3	672,500	3	4	3.4 : 1.14	4.35 : 1.4	5.15 : 1.7	960	226			
	695,700		6								
DBM-5	927,200	5	4	3.4 : 1.14	2.75 : 0.9	3.25 : 1	1050	263			
	952,400		6								

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境

10